

# Yparex® 9601

Provisional data sheet

Property data

**PE-LLD**  
Modified

Visit us at [www.yparex.com](http://www.yparex.com)  
Version 1.1, issue date 1-7-2012

Properties	Typical Data	Unit	Test Method
------------	--------------	------	-------------

## RHEOLOGICAL PROPERTIES

Melt flow index MFI (190°C, 2,16 kg)	1,3	g/10 min	ISO 1133
--------------------------------------	-----	----------	----------

## THERMAL PROPERTIES

Melting temperature (10°C/min)	125	°C	ISO 11357-1/-3
Vicat softening temperature (50°C/h 10N)	105	°C	ISO 306


## OTHER PROPERTIES

Density	928	kg/m <sup>3</sup>	ISO 1183
---------	-----	-------------------	----------

## RHEOLOGICAL CALCULATION PROPERTIES

Enthalpy of melting	130	kJ/kg	ISO 11357-1/-3
---------------------	-----	-------	----------------

## VISCOSITY-SHEAR RATE



All information supplied by or on behalf of Yparex BV in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and, in good faith, believed reliable, but Yparex BV assumes no liability and makes no warranties of any kind, explicitly or implied, including, but not limited to, those of title, merchantability, fitness for a particular purpose or non-infringement or any warranty arising from a course of dealing, usage, or trade practice whatsoever in respect of application, processing or use made of the aforementioned information or product. The user assumes all responsibility for the use of all information provided and shall verify quality and other properties or any consequence from the use of all such information. Typical values are indicative only and are not to be construed as being binding specifications.